

Voltex HeNe Laser Power Supply

Model E-15-NN-LP



The Voltex “NN” series of DC input power supplies represents the state of the art in compact, ultra-high reliability switching power supplies. This series has been given a 7 element input filter to eliminate ripple and noise at the input. It has also had the output re-designed to reduce output ripple and noise to near zero. This power supply:

- Exhibits virtually no noise at either input or output.
- Operates most 1/2 mW through 2 mW HeNe lasers.
- Delivers > 80% conversion efficiency for cool operation and long life.
- At 1” X 1 1/2” X 3 3/4”, occupies only 5.6 cubic inches.
- Has an internal bleed-down resistor to reduce shock hazard.
- Has a full 18-month warranty.

For further information, pricing and delivery, please contact:

Voltex, Inc.
2336 East Platte Ave
Colorado Springs, CO
80909

Tel: (719) 599-0531
Fax: (719) 599-7851
E-mail: info@voltex.net
Website: www.voltex.net

E-15-NN-LP SPECIFICATIONS

Input:

Input Volts:	10 - 14 VDC
Input Current:	2 A Max. *
Lead Length:	12" minimum (304mm)
Operating Ambient Temp:	-20 to +50 deg C
Input current ripple	Virtually unmeasurable

Agency approvals:

TUV certified to UL, IEC 60950-1

Output:

Voltage:	1100-1500 VDC
Current:	3 to 6.5 mA. User adjustable
Start Voltage:	>8 KV
Output Current Ripple:	Virtually unmeasurable **
Output Fault Protection:	Open, Short, Arc
Conversion Efficiency:	> 80%
CDRH Delay:	3 – 7 seconds. (Cut violet loop to disable)
TTL Enable	Ground to enable
Output Connector:	Alden style, high voltage
Dimensions:	1" X 1.5" X 3.75" (25mm X 38mm X 95mm)

* Input Current varies with line and load. Starting inrush may exceed this.

** Let us know if you get different results.



