

# Voltex HeNe Laser Power Supply

Model E-15-00



The Voltex E series of DC input power supplies represents the state of the art in compact, ultra-high reliability switching power supplies. This series offers a full range of features including CDRH delay, user adjustable current, and an open-collector disable input ("TTL" control). Designed to provide very high conversion efficiency, and fully encapsulated in a specially formulated epoxy for maximum heat dissipation and electrical insulation, these power supplies can be packaged in a much more compact and convenient size than our competitors without compromising reliability. This power supply:

- Operates most 1/2 mW through 2 mW HeNe lasers.
- Delivers > 80% conversion efficiency for cool operation and long life.
- At 1" X 1 1/2" X 3 3/4", occupies only 5.6 cubic inches.
- Has an internal bleed-down resistor to reduce shock hazard.
- Has a full 18-month warranty.

For further information, pricing and delivery, please contact:

Voltex, Inc.  
2336 East Platte Ave  
Colorado Springs, CO  
80909

Tel: (719) 599-0531  
Fax: (719) 599-7851  
E-mail: [info@voltex.net](mailto:info@voltex.net)  
Website: [www.voltex.net](http://www.voltex.net)

# E-15-00 SPECIFICATIONS

## Input:

Input Volts:	10 - 14 VDC
Input Current:	2 A Max. *
Lead Length:	12" minimum (304mm)
Operating Ambient Temp:	-20 to +50 deg C

## Output:

Voltage:	1100-1800 VDC
Current:	3 to 6.5 mA. User adjustable
Start Voltage:	>8 KV
Output Current Ripple:	< 1% P – P ( < .5% RMS ) **
Output Fault Protection:	Open, Short, Arc
Conversion Efficiency:	> 80%
CDRH Delay:	3 – 5 seconds. (Cut violet loop to disable)
TTL Enable	Ground to enable
Output Connector:	Alden style, high voltage
Dimensions:	1" X 1.5" X 3.75" (25mm X 38mm X 95mm)

\* Input Current varies with line and load.

\*\* Measured current ripple will vary with type of laser and current setting.

